



Bubble Breaker

Additive
CONVENTIONAL

Always test ink on substrate prior to production run. Please refer to the MSDS for safety precautions.

Description: The Bubble Breaker 2032 breaks bubbles, improves flow, and aids in the evaporation of solvent from ink or paint film. When the Bubble Breaker is added to an ink, it becomes completely distributed throughout the applied ink film. Therefore, it works from the bottom up to release any residual air from the film. It demonstrates profound effectiveness in alkyd, vinyl, and epoxy systems. Substantial effect may be seen in other systems as well.

Qualities:

- Break Bubbles
- Improves Flow
- Speed Up the Evaporation
- Ease of Application
- Compatible with most of Deco-Chem's Inks

Mixing: A suggested concentration is 1/2 to 1 % by weight, or about 3 tablespoons of the Bubble Breaker 2032 per gallon of ink. In some systems only 0.1 % is needed for sufficient flow.

If our current line of colors, finishes, or textures does not meet your needs-
Contact us today about tailoring a product for you!

The information and recommendations contained in this product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on present knowledge and believe to be accurate. Information is based on technical data which the Seller believes to be reliable, and are intended for use by persons having skill and knowledge, at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent. Company policy of continuous product improvement might change the information contained in this product information sheet and users are requested to ensure that they follow current recommendations.

