



Dry Erase

CONVENTIONAL

Always test ink on substrate prior to production run. Please refer to the MSDS for safety precautions.

Description: This material, when properly cured is a rigid transparent coating with outstanding chemical resistance. Use dry erase markers or any water based markersto mark the surface. They are easily removed by wiping with a dry cloth or tissue without marring the surface. The ink has excellent weatherability, gloss, abrasion resistance and ease of print.

- Qualities:**
- Excellent Flexibility
 - Durability
 - Easily Removable
 - Chemical Resistant
 - Excellent Gloss
 - Abrasion Resistant
- Substrates:**
- Glass
 - Mill Finish Aluminum
 - Metal
 - Epoxy Primed Aluminum
 - Anodized Aluminum
 - Stainless Steel

Stencil: Use a Lacquer Proof or Direct Emulsion Film, Photographic, or Water-soluble Hand-cut Stencils

Coverage: 1,200-1,500 sq/ft. per gallon depending on ink deposit

Screen: 305 Mesh recommended for most applications.

Cure Parameters: Bake at 400 F for 4 minutes.

Additives: MBI-31 and MBI-49 Flow Agent, MBI-94 Thinner, and MBI-95 Retarder

Cleaner: MBI-96 Screen Wash

Storage: Store tightly shut in a cool, dry, and dark place for minimum shelf life for 6-12 months.

Sizes: 1 Gallon Pail, 5 Gallon Pail, 30 Gallon Drum, 55 Gallon Drum

Products: D-10577 Clear

If our current line of colors, finishes, or textures does not meet your needs-
Contact us today about tailoring a product for you!

The information and recommendations contained in this product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on present knowledge and believe to be accurate. Information is based on technical data which the Seller believes to be reliable, and are intended for use by persons having skill and knowledge, at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent. Company policy of continuous product improvement might change the information contained in this product information sheet and users are requested to ensure that they follow current recommendations.

