



Deco-Chem's Frosty Look Inks  
Conventional Screen Inks

Always test ink on substrate prior to production run. Please refer to the MSDS for safety precautions.

**Description:** The Frosty Conventional Screen Inks are tough, low odor plastics and metals inks. Ease of application is one of the most distinctive characteristics of these Frosty Conventional Screen Inks. The smooth and light consistency allows a clean cutting action during the squeegee traverse. The solvent blend of the Frosty Conventional Screen Inks is formulated so that the printed film becomes completely dry after controlled exposure to jet drying or baking conditions.

**Qualities:**

- Appliance Approved
- Low Odor
- Tough
- Excellent Solvent Resistance
- Excellent Block Resistance
- Ease of Application

**Substrates:**

- Glass
- Metals
- Vinyls
- Styrene Noryl
- Polycarbonates
- Plastics

**Stencil:** Use a lacquer proof or direct emulsion film, photographic, or water-soluble hand-cut stencils

**Coverage:** 400 - 500 sq/ft. per gallon depending on ink deposit

**Application:** Deco-Chem's Frosty Conventional Screen Inks are engineered to be directly screened onto the substrate using a 65 - 260 mesh screen.

**Cure Parameters:** For air dry, air dries in 4 - 20 minutes depending on racking procedure and shop conditions. For bake dry, baking at 250 - 450 degrees F for 1 - 30 minutes.

**Additives:** ATX50 Flow Additive, ATX94 Thinner, and ATX95 Retarder

**Cleaner:** ATX96 Wash-up

**Storage:** Store tightly shut in a cool, dry, and dark place for maximum shelf life for 6-12 months.

**Sizes:** 1 Gallon, 5 Gallon Pail, 30 Gallon Drum, 55 Gallon Drum

**Related Products:** 6295 Silver Frost 7626 Frost

If our current line of colors, finishes, or textures does not meet your needs-  
Contact us today about tailoring a product for you!

The information and recommendations contained in this product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on present knowledge and believe to be accurate. Information is based on technical data which the Seller believes to be reliable, and are intended for use by persons having skill and knowledge, at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent. Company policy of continuous product improvement might change the information contained in this product information sheet and users are requested to ensure that they follow current recommendations.

