



Loxon for Coilcoat - LOX/C

Epoxy
CONVENTIONAL

Always test ink on substrate prior to production run. Please refer to the MSDS for safety precautions.

Description: Loxon, the “work horse” of the appliance industry, is a blend of “high tech” polymers specifically synthesized and produced for metal decorating applications. Loxon has been developed to meet new appliance specifications. It has superior resistance to laundry group detergents and the new generation spot removers. Loxon has passed virtually all other chemical resistance tests called for in the appliance industry.

- Qualities:**
- Appliance Approved
 - Abrasion Resistant
 - Opaque
 - Flexible
 - Chemical Resistant
 - Excellent Adhesion
- Substrates:**
- Metal
 - Glass
 - Mill Finish Aluminum
 - Steel
 - Epoxy Sized Alluminum
 - Anodized Aluminum
 - Brass
 - Stainless Steel

Coverage: 1,200-1,500 sq/ft. per gallon depending on ink deposit

Wire Rod: Rod#32 is recommended

Application: Heavy Body Clear 1133 can be applied by roll/coil coating. The coating is provided at ready-to-use viscosity. Pretests are recommended prior to production run.

Cure Parameters: 400 F at 3 minutes

Additives: 2031 Bubble Breaker, LOX31 and LOX49 Flow Agent, LOX94 Thinner, and LOX95 Retarder

Cleaner: LOX96 Wash-up

Storage: Store tightly shut in a cool, dry, and dark place for minimum shelf life for 6-12 months.

Sizes: 1 Gallon, 5 Gallon Pail, 30 Gallon Drum, 55 Gallon Drum

Products: Topcoats, primers, and colors. Please inquire.

If our current line of colors, finishes, or textures does not meet your needs-
Contact us today about tailoring a product for you!

The information and recommendations contained in this product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on present knowledge and believe to be accurate. Information is based on technical data which the Seller believes to be reliable, and are intended for use by persons having skill and knowledge, at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent. Company policy of continuous product improvement might change the information contained in this product information sheet and users are requested to ensure that they follow current recommendations.

