



Myflex - MFX

Air Dry for Plastic
AIR/CONVENTIONAL

Always test ink on substrate prior to production run. Please refer to the MSDS for safety precautions.

Description: The Myflex series is a unique and sophisticated blend of polymers that demonstrates unusual toughness, flexibility, adhesion, gloss, and weatherability. The nature of the system requires uncommon solvents to achieve solution. As a result, the printed film has resistance to a variety of solvents and chemicals. Myflex is especially formulated for and has a natural adhesion to raw polyester film such as Mylar.

- Qualities:**
- Excellent Gloss
 - Chemical Resistant
 - Tough/Durable
 - Ease of Application
 - Flexible
 - Natural Adhesion
- Substrates:**
- Mylar
 - Plastic
 - Polyester
 - Aluminum

Stencil: Use a Lacquer Proof or Direct Emulsion Film, Photographic, or Water-soluble Hand-cut Stencils

Coverage: 1,200-1,500 sq/ft. per gallon depending on ink deposit

Screen: 200 to 300 mesh recommended for most applications.

Cure Parameters: Air dry will tough in 15 to 25 minutes, force dry 3 to 4 minutes at 175 F, or bake 1 minute at 350 F.

Additives: MFX94 Thinner and MFX95 Retarder

Cleaner: MFX96 Screen Wash

Storage: Store tightly shut in a cool, dry, and dark place for minimum shelf life for 6-12 months.

Sizes: 1 Gallon, 5 Gallon Pail, 30 Gallon Drum, 55 Gallon Drum

If our current line of colors, finishes, or textures does not meet your needs-
Contact us today about tailoring a product for you!

The information and recommendations contained in this product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on present knowledge and believe to be accurate. Information is based on technical data which the Seller believes to be reliable, and are intended for use by persons having skill and knowledge, at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent. Company policy of continuous product improvement might change the information contained in this product information sheet and users are requested to ensure that they follow current recommendations.

