



# Pearlescent

Flexographic Ink  
UV

Always test ink on substrate prior to production run. Please refer to the MSDS for safety precautions.

**Description:** The Pearlescent Inks can be utilized for the package and product label market. They are compatible with Deco-Chem's flexo inks. The Pearlescent Inks are a one part system ready to print straight from the can.

- Qualities:**
- High Gloss
  - Excellent Opacity
  - IPA Resistant
  - Abrasion Resistant
  - Intercoat Adhesion
  - Fast Cure

- Substrates:**
- Films
  - Vinyl
  - Paper
  - Cardstock
  - PVC

**Stencil:** Use a lacquer proof or direct emulsion film, photographic, or water-soluble hand-cut stencils

**Coverage:** 2,000 - 4,000 sq/ft. per gallon depending on ink deposit

**Application:** The Pearlescent Inks need to be shaken thoroughly prior to use. The ink is provided at ready to print viscosity. UV Pearlescent Screen Inks are designed to printed using 200 - 1500 line anilox.

**Cure Parameters:** The Pearlescent Inks cure only by UV light of the proper wavelength. Cure speeds depend on ink deposit, color shades, bulb selection, and energy level.

**Additives:** 077-37 Thinner, 682-39 and 743-39 Photoinitiators

**Cleaner:** FXM96 Wash-up

**Storage:** Store tightly, shut in a cool, dry, and dark place for minimum shelf life for 6-12 months.

**Sizes:** 1 Gallon Pail, 2 Gallon Pail, 5 Gallon Pail

- Products:**
- |         |                     |
|---------|---------------------|
| CMF0750 | Aironet White Pearl |
| CMF1131 | Pearl White         |
| CMF1426 | Pearlized Vanish    |
| CMF1527 | Pearlescent HVFEXT  |

If our current line of colors, finishes, or textures does not meet your needs-  
Contact us today about tailoring a product for you!

The information and recommendations contained in this product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on present knowledge and believe to be accurate. Information is based on technical data which the Seller believes to be reliable, and are intended for use by persons having skill and knowledge, at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent. Company policy of continuous product improvement might change the information contained in this product information sheet and users are requested to ensure that they follow current recommendations.

