



Deco-Chem's Sublimation Ink  
UV Curable Sublimation Ink

Always test ink on substrate prior to production run. Please refer to the MSDS for safety precautions.

**Description:** The UV Sublimation Ink provides superior adhesion for transferring images in the sublimation process. Simply screen prints the ink where you will be transferring your dye image, UV cure it, and transfer as normal.

**Qualities:**

- Excellent Adhesion
- Excellent Flexibility
- Ease of Print
- Excellent Abrasion Resistant
- Excellent Flow
- Long-Term Durability

**Substrates:**

- Glass
- Metals

**Stencil:** Use a lacquer proof or direct emulsion film, photographic, or water-soluble hand-cut stencils

**Coverage:** 2,500 - 4,000 sq/ft. per gallon depending on ink deposit

**Application:** Deco-Chem's UV Sublimation Ink is engineered to be directly screened onto the substrate using a 330 mesh.

**Cure Parameters:** Curing will change based on substrate, film thickness, and UV reactor being used. UV Sublimation Ink works well when cured with one 300 watt/inch medium pressure vapor bulb at a rate of 30 - 50 fpm and a heat pump.

**Additives:** DRM48 Flow Additive, DRM94 Thinner, and DRM98 Adhesion Promoter

**Cleaner:** 3883 Screen Wash

**Storage:** Store tightly shut in a cool, dry, and dark place for maximum shelf life for 6-12 months.

**Sizes:** 1 Gallon, 5 Gallon Pail, 30 Gallon Drum, 55 Gallon Drum

**Related Products:** D-10244 UV Metal Primer

If our current line of colors, finishes, or textures does not meet your needs-  
Contact us today about tailoring a product for you!

The information and recommendations contained in this product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on present knowledge and believe to be accurate. Information is based on technical data which the Seller believes to be reliable, and are intended for use by persons having skill and knowledge, at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent. Company policy of continuous product improvement might change the information contained in this product information sheet and users are requested to ensure that they follow current recommendations.

